

PRIMOS

UTILIGHT

SPARK

INFORMATION SIGNS

Information signs with **HYBRYD** emergency light luminaires allows presentation of additional information in public spaces.

It is possible to perform single-sided or double-sided luminaires and mounting to the wall or directly to the ceiling. A wide range of mounting accessories is available.

Thanks to the use of information signs with **HYBRYD** luminaires, they are possible to illuminate and connect them to a central or group power supply system.



20x10cm 30x15cm 40x20cm 100x15cm 40m



SIGNS AND SYMBOLS





Other signs on special order

HABBAD

MOUNTING TYPES AND ACCESORIES

SPARK SGN LED

W1 - back to the wall



W137 – longer side to the ceiling or to the wall with the possibility of setting the angle 0 – 90°



PRIMOS family of luminaires





Double-sided flag for W121 – to wall or PRIMOS **SS** ceiling ceiling by the shorter side with angle adjustment 0° – 90° mounted



W221 - mounted with its shorter side to the ceiling or to the wall with the possibility of setting the angle 0° - 90°



W122 - to wall or ceiling by the longer side with angle adjustment 15° – 90°



W222 - mounted with its longer side to the ceiling or to the wall with the possibility of setting the angle 0° - 90°



UTILIGHT SGN LED

W140 - back to the wall




C142 - directly to the C145 - recessed ceiling




UTILIGHT W141 semaphore

UTILIGHT C143 – suspended with cords and easy height adjustment



UTILIGHT C144 – suspended with cords or chains



DIMENSIONS

	SPARK	PRIMOS	UTILIGHT
Available sign dimensions	30x15cm, 40x20cm	30x15cm	20x10cm, 30x15cm, 40x20cm

MATERIALS

	SPARK	PRIMOS	UTILIGHT	
Housing material	powder coated aluminum	PC/ABS mix	powder coated aluminum	
Housing colour	 ○ RAL 9003 ◎ RAL 9006 ● RAL 9005 ^{•)} 	() RAL 9016	 RAL 9003 RAL 9006 RAL 9005 *) 	
Lamp shade material	PC	PC	clear PMMA	
*) possible to varnish on any other colour				

SUPPLY VOLTAGE

230V AC and versions with power failure operation.